

# Realtime T110 access with Camera + ST10

Professional Fingerprint Access Control with Exit fingerprint Reader



## Specifications

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>» Reader</li> <li>» Proximity Card</li> <li>» Display</li> <li>» Keyboard</li> <li>» Interface</li> <br/> <li>» Camera</li> <li>» TF Card (Micro- SD)</li> <li>» Additional Feature</li> <li>» Temperature</li> <li>» Humidity</li> <li>» Operation</li> <li>» Registration Capacity</li> <li>» Passwords Authentication</li> <li>» Methods</li> <li>» Authentication Languages</li> <li>» Access Control</li> <br/> <li>» Multi Door Access</li> <br/> <li>» Alarm</li> <li>» Auto Self-check</li> <li>» FAR/FRR</li> <li>» FP Verification Speed</li> <li>» FP Verification Angle</li> <li>» Smart FP Update</li> </ul> | <p>Optical Fingerprint Reader, Dual Fingerprint Reader (Optional)<br/>           EM, MIFARE Card (Optional)<br/>           2.8" TFT True Color LCD<br/>           16 Keys (with backlight), 1 Door Bell Button<br/>           Power Port (9V - 12V; GND)<br/>           TCP/IP, RS232/485, Wi-Fi (Optional)<br/>           Wiegand 26/34 bits with 1 In &amp; 1 Out<br/>           Door Relay Output (COM:NO;NC)<br/>           Duress Alarm Output (COM:NO;NC)<br/>           Door Bell Button Input (PUSH; GND)<br/>           Door Lock On/Off Input<br/>           Door Bell Output<br/>           Anti Pass Back Port (TXD, TXD, GND)<br/>           (Real Time Photo Taking)<br/>           (Photo Storage)<br/>           Reset Button<br/>           -10°C - +60°C<br/>           20% - 80%<br/>           One-way, Two-way, Multi Door/ Network<br/>           Normal: 1000FP / 1000 Cards / 1000<br/>           Fingerprint, EM Card, Password, Dual Fingerprint,<br/>           Group Combination<br/>           English<br/>           Able to control single door access through Wiegand, 50 time periods, Time setting authentication, Anti Pass Back,<br/>           Sending attendance records by real time to Server or PC, Support Dual Fingerprint or Group Combination Authentication<br/>           5 Door Access Control (1 Door controlled by a Fingerprint Machine, 4 Doors controlled by 4 Fingerprint Readers<br/>           connected by Fingerprint, Machine through RS232/485)<br/>           Force Removal Alarm, Duress Alarm, Force Door Open Alarm, Overtime Alarm<br/>           Yes<br/>           0.00001% / 0.1%<br/>           1.0 s (with 2000 FP registration)<br/>           0° - 360°<br/>           Yes</p> |
|--|--|

## Features

