

Realtime T26

Touch Button Big Display Attendance Recorder



Specifications

» Dimensions	L165 x W170 X H43 (mm)
» Operation	Offline
» Power Supply	DC9V/DC5V
» Authentication Methods	FP, PIN, RFID, FP + RFID, FP + PIN + RFID
» Fingerprint Verification Mode	1:1, 1:N
» Fingerprint Sensor Area	16 x 14 (mm)
» Verification Speed	≤ 1.2s
» Max. Fingerprint Records	1,000
» Max. Management Records	10,000
» Max. Attendance Records	100,000
» Display	3.2" TFT True Color LCD 320 x 240 Pixels
» Display Language	English
» Smart FP Update	Yes
» Attendance Record Check	Press OK Button for Checking
» Backup Battery	≤ 4 Hours (Optional)
» Interface	USB Link, USB Disk, TCP/IP
» Proximity Card	EM Card / MIFARE Card (Optional)



Features



Realtime T6c

Card Based Attendance Recorder



Specifications

» Working Voltage	DC9V/DC5V
» Identify Ways	Proximity card, password
» Recognition Speed	≤ 1 s
» Work card storage Capacity	2000
» Management Record Capacity	2000
» Record Capacity	50,000
» Screen Display:	Blue backlight, high-resolution LCD screen (128 × 64 dot matrix)
» Languages	English
» Blackout attendance	≥ 4 hours (B type)
» Means of communication	USB-Device Communication (basic) SD card upload and download data (Basic) TCP / IP communication



Features

