

## Realtime T32 with camera

Biometric with Camera Attendance Recorder  
with Simple access Control System



### Specifications

» Dimensions	L 198 x W 128 x H 43 (mm)
» FRR	≤ 0.01%
» FAR	≤ 0.0001%
» FP Recognition speed	1 sec
» Capacity	5000 pc
» Transaction Memory Capacity	200,000
» Images Installer	25000
» Verification Modes	1 : 1 OR 1 : N
» Authentication Methods	FP, PIN, RFID, FP + PIN, FP + PIN + RFID
» Operation Mode	Standalone or connect with PC via LAN or WAN
» Communications	RS232/485, TCP/IP, USB Drive, Wi-Fi/ GPRS
» Operation Power	< 5W
» Power Input	DC 12V
» Weight	1.2KG
» Display	QVGA 76800 pixels color backlit LCD
» Image Capture	Instant Photo-taking with built-in camera
» Image Display	Support Image Retrieval & Display
» Languages	English
» Voice	English
» Access control Feature	Standard with Time Zone Management
» Attendance Checking	Any staff may check own attendance

### Features



## Realtime RTS10

Fingerprint with RF Standalone Access Control



### Specifications

» Standby Voltage	< 100mA
» Relay Tolerance	3A
» Operating Temperature	-10° to 50°
» Operating Humidity	20%RH-60%RH
» Fingerprint Templates	500
» EM Card Templates	500
» PIN Templates	500
» No. of Administrator	10
» Access Storage	80,000
» Access Control Time Zone	8
» Collector Resolution	450 DPI
» Fingerprint Time	< 1 s
» Identification Time	< 1 s
» False Acceptance Rate	< 0.0001%
» False Recognition Rate	< 0.01%
» Dimension	145 x 80 x 30 (mm)
» Weight	100 g

### Features

