

## Realtime T74

Facial Recognition Time Attendance



500  
Users

### Specifications

|                              |   |
|------------------------------|---|
| » CPU                        | Samsung 2440  |
| » Camera                     | Special Dual-Camera   |
| » Authentication Method      | Face Only, Face Capture   |
| » Anger Range                | > Horizontal; $\pm 20^\circ$ , Vertical $\pm 27^\circ$  |
| » Fitting Height             | > 145-195 cm  |
| » Working Distance           | > 30-80 cm  |
| » User Capacity              | 500   |
| » Record Capacity            | 200,000 records   |
| » I/O (1 input and 1 output) | Switch Signal supported   |
| » Function Key               | Max. 10 function keys, User Customized Red (Alarm / Failed), Green (Running / Successful), Yellow (Power) |
| » Language                   | English   |
| » Working Environment        | Illumination: 0-20000LUX; Water Proof Class 3; Dust Proof Class 6   |
| » Working Humidity           | 20%-80%   |
| » Working Temperature        | -20--45°C   |
| » Installation               | Wall Mounting   |



### Features



## Realtime T4D Controller

4 Door Access Controller



### Specifications

|                               |   |
|-------------------------------|---|
| Working Mode                  | offline/online                          |
| Verification                  | ID Card, password                       |
| Combination                   | pin+ card, pin, card                    |
| Card Capacity (pcs)           | 18,000                                  |
| Attendance Record             | 100,000                                 |
| Controller to Reader distance | 80-100m                                 |
| Door Control                  | 4Door                                   |
| Communication                 | TCP/IP                                  |
| RFID Reader                   | Support HID, CPU, Motorola brand reader |
| Reader format                 | WG26/34                                 |
| Working Humidity              | 10%~90%                                 |
| Working Temperature           | -40°C ~70°C                             |
| Power Supply                  | 12V DC , Idle Current: 4A, 48watt       |
| Database                      | Access / SQL                            |
| Sound indicator               | Buzzer                                  |
| Dimension                     | 218mm*106mm                             |

