

MD 1508 15 series, 8 Channel DVR



FEATURES:

- H.264 compression.
- No. of Video/Audio Channels- 8V/4A.
- Real time display & recording HD1 @ 200FPS.
- CIF resolution and D1 selectable.
- DVR supports direct data card & 3G Mobile networks.
- Free domain name service.
- Plug n Play.
- Search type file list & event list.
- Internal storage 2TB.

SPECIFICATIONS:

MD1508		
Video & Audio		
Video Input	8 Composite Video 0.5~1V p-p 75 Ohm Auto Termination	
Display	Resolution	720x576 Pixel PAL & 720x480 Pixel NTSC
	Frame Rate	200FPS PAL / 240FPS NTSC
	Mode	1/4/9/Sequence
Operating System	Embedded Linux	
Video Compression	Standard H.264 Baseline	
TV System	NTSC / PAL	
Operation	Pentaplex	
User Interface	Graphical User Interface.	
Record Settings		
Main Stream	Record Rate	PAL Up to 200 FPS @ 352x288 (CIF) / NTSC Up to 240FPS @ 352x240 (CIF) PAL Up to 200 FPS @ 704x288 (HD1) / NTSC Up to 240FPS @ 704x240 (HD1) PAL Up to 96 FPS @ 704x576 (D1) / NTSC Up to 120FPS @ 704x480 (D1)
	Video Quality	Very Low, Low, Medium Low, Medium High, High & Very High VBR / CBR selectable
Schedule	Manual, Schedule & Motion (Pre Recording)	
Search & Playback	Search Type	Event & Motion file List
	Playback Ch/FPS	8CH @ 200FPS
	Playback Tools	Fast forward/Backward x2, x4, x6 x8 Audio Enable / Disable
Backup	Backup can support USB Flash Drive & USB HDD-500GB (Fat-32 Format)	
Network Settings (IPv4)		
Sub stream	Transfer Rate	N/A
	Bandwidth control	
Network protocol	TCP/IP, HTTP, DHCP, DDNS, PPPoE & SMTP	
DDNS Service	Free Service: ddns.magussecure.in	
Online User	10 User	
Storage		
HDD Interface & Number of port	SATA Interface & 1port	
HDD Capacity	Maximum 2TB	
Overwrite Mode	Auto over write FIFO / Stop Recording	
External Interface		
Video Output	BNC 1 Composite Video 1V p-p	
VGA Resolution	SVGA 800x600, XGA 1024x768	
Audio I/O	RCA 4Ch Input & 1Ch output	
Alarm I/O	N/A	
Network	10/100Mbps - RJ45	
USB Port	Front1 & Rear 2 (USB 2.0)	
Communication port	RS-485 Telemetry Control	
Telemetry Protocols	Lilin, Pelco-D & Pelco-P, Samsung (Supports 13 protocol's)	
User Application		
Monitoring	64Ch Client Viewer & Browser Supported IE, Google Chrome, Mozilla Firefox & Avant	
Mobile View / OS Support	iPhone, Android, Window, Blackberry & Symbian	
Security	Password Protection	
Alert Type	Internal buzzer for HDD Full & HDD Error	
General		
Product Dimensions	250mm X 50mm X 245mm (W x H x D)	
Box dimensions	322mm X 113mm X 304mm (W x H x D)	
Gross weight	1600gm	
Power Supply	Input 100~240V Ac , 50/600Hz & Output 12V DC 2Amp	
Accessories	USB Mouse, HDD SATA & Power Cable, Screw, Quick reference Guide, Software CD & Remote control	
Environment		
Temperature & Humidity	+0°C ~ +40°C (+32°F ~ +104°F) / 20% ~ 85% RH	