

## MD 1516 15 series, 16 Channel DVR



### FEATURES:

- H.264 compression.
- No. of Video/Audio Channels- 16V/16A.
- Real time display & recording HD1 @ 400FPS.
- CIF resolution and D1 selectable.
- DVR supports direct data card & 3G Mobile networks.
- Free domain name service.
- Plug n Play.
- Search type file list & event list.
- Internal storage 4TB.
- Support on screen PTZ control & digital zoom.

## SPECIFICATIONS:

<b>MD1516</b>		
<b>Video &amp; Audio</b>		
<b>Video Input</b>	16 Composite Video 0.5~1V p-p 75 Ohm Auto Termination	
<b>Display</b>	<b>Resolution</b>	720x576 Pixel PAL & 720x480 Pixel NTSC
	<b>Frame Rate</b>	400FPS PAL / 480FPS NTSC
	<b>Mode</b>	1/4/9/16/Sequence
<b>Operating System</b>	Embedded Linux	
<b>Video Compression</b>	Standard H.264 Baseline	
<b>TV System</b>	NTSC / PAL	
<b>Operation</b>	Pentaplex	
<b>User Interface</b>	Easy Advance Graphical User Interface.	
<b>Record Settings</b>		
<b>Main Stream</b>	<b>Record Rate</b>	PAL Up to 400 FPS @ 352x288 (CIF) / NTSC Up to 480FPS @ 352x240 (CIF) PAL Up to 272 FPS @ 704x288 (HD1) / NTSC Up to 320PS @ 704x240 (HD1) PAL Up to 128 FPS @ 704x576 (D1) / NTSC Up to 160FPS @ 704x480 (D1)
	<b>Video Quality</b>	Lowest, Low, Common, Medium High & Highest VBR / CBR selectable
<b>Schedule</b>	Manual, Schedule, Motion & Alarm (Pre Recording )	
<b>Search &amp; Playback</b>	<b>Search Type</b>	Calendar (Date & time), Event, Motion, Alarm
	<b>Playback Ch/FPS</b>	16CH @ 400FPS
	<b>Playback Tools</b>	Fast forward/Backward x2, x4, x6 x8 Audio Enable / Disable
<b>Backup</b>	Backup can support USB Flash Drive & USB HDD-500GB (Fat-32 Format)	
<b>Network Settings (IPv4)</b>		
<b>Sub stream</b>	<b>Transfer Rate</b>	PAL Up to 80 FPS @ 352x288 (CIF) / NTSC Up to 80FPS @ 352x240 (CIF)
	<b>Bandwidth control</b>	
<b>Network protocol</b>	TCP/IP, HTTP, DHCP, DDNS, PPPoE & SMTP	
<b>DDNS Service</b>	Free Service: <a href="http://ddns.magussecure.in">ddns.magussecure.in</a>	
<b>Online User</b>	10 User	
<b>Storage</b>		
<b>HDD Interface &amp; Number of port</b>	SATA Interface & 2port	
<b>HDD Capacity</b>	Maximum 4TB	
<b>Overwrite Mode</b>	Auto over write FIFO / Stop Recording	
<b>External Interface</b>		
<b>Video Output</b>	BNC 1 Composite Video 1V p-p	
<b>VGA Resolution</b>	SVGA 800x600, XGA 1024x768 & 1280x1024	
<b>Audio I/O</b>	RCA 16Ch Input & 1Ch output	
<b>Alarm I/O</b>	Alarm Input-4ch & Alarm Output-1Ch	
<b>Network</b>	10/100Mbps - RJ45	
<b>USB Port</b>	Front 1 & Rear 2 (USB 2.0)	
<b>Communication port</b>	RS-485 Telemetry Control	
<b>Telemetry Protocols</b>	Lilin, Pelco-D & Pelco-P, Samsung (Supports 13 protocol's)	
<b>User Application</b>		
<b>Monitoring</b>	64Ch Client Viewer & Browser Supported IE, Google Chrome, Mozilla Firefox & Avnat	
<b>Mobile View / OS Support</b>	iPhone, Android, Window, Blackberry & Symbian	
<b>Security</b>	Password Protection	
<b>Alert Type</b>	E-mail Alert & External alarm Output for Video Loss, Motion Alarm, HDD Full & Sensor Input	
<b>General</b>		
<b>Product Dimensions</b>	378mm X 60mm X 305mm (W x H x D)	
<b>Box dimensions</b>	415mm X 135mm X 375mm (W x H x D)	
<b>Gross weight</b>	3320gm	
<b>Power Supply</b>	Input 100~240V Ac 50/60Hz & Output 12V DC 4Amp	
<b>Accessories</b>	USB Mouse, HDD SATA & Power Cable, Screw, Quick reference Guide, Software CD & Remote control	
<b>Environment</b>		
<b>Temperature &amp; Humidity</b>	+0°C ~ +40°C (+32°F ~ +104°F) / 20% ~ 85% RH	